

Insulating

[Volu-Matic® III
Gas, Diesel or Power
Take-Off](#)

[Volu-Matic® III Electric](#)

[Volu-Matic® IV](#)

[Volu-Matic® V](#)

[Attic-Matic™](#)

[Multi-Matic™](#)

[Multi-Tank™](#)

[Force/2™](#)

[Dual-Matic](#)

[Insulation Removal
Vacuum](#)

Force/2™

The Force/2™ is a solid performer that is dependable and easy to use. It is the only portable insulation machine capable of blowing more than 2000 pounds of material per hour. Because no insulation material passes through the blower, the Force/2 is a virtual workhorse, requiring only minimal maintenance. Direct drive transmission means there are no chains, sprocket or pulleys to adjust or wear out, ever.

The Force/2 machine can be set up on the jobsite in a matter of minutes, and at the end of the day clean up is equally efficient. The standard machine comes ready with all accessories so you're able to start blowing right away.



Force / 2™

Specifications

Overall Dimensions:

Height: 42 inches (106.68 cm)

Diameter: 32 inches (81.28 cm)

Weight:

275 lbs. (124.7 kg)

Hopper Capacity:

50 lbs. Cellulose (22.68 kg)

15 lbs. Fiber Glass (6.80 kg)

Production Rates:

Fiber Glass:

8–10 lbs. (3.6-4.5 kg) per minute

Rockwool:

N/A

Cellulose:

30–40 lbs. (13.6-18.1 kg) per minute

The above rates are based on using 100 feet of 3-inch hose at a 2 story lift.