



MATERIAL SAFETY DATA SHEET

SECTION 1- PRODUCT IDENTIFICATION

MANUFACTURER: Lamtec Corporation

ADDRESS: 5010 River Road Mount Bethel, Pennsylvania 18343-5610

TELEPHONE: 570-897-8200

DATE OF PREPARATION: 8/24/2010

PRODUCT NAMES: R-3035, R-3035 Black, R-3035 4x4, R-3050, R-3070, R-3070 Black
R-3035 Black, R-3035 HD, R-3035 HD Black, R-3035 DB,
R-3035 DN, RC-3035, 30J, L-4535A, RA-3035, DB-125

SECTION 2- HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

<u>PRODUCT INGREDIENTS:</u>	<u>CAS NUMBER</u>	<u>TLV/PEL</u>
Aluminum Foil	7429-90-5	-
Fiberglass Yarn Reinforcing	65997-17-3	15.0 mg/m ³
Kraft Paper	-	-
Polymeric Adhesive		

<u>HAZARDOUS INGREDIENTS*</u>	<u>CAS Number</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OTHER LIMITS RECOMMENDED</u>
Antimony Oxide	1309-64-4	0.5 mg/m ³	0.5 mg/m ³	
Hydrated Alumina	21645-51-2	15.0 mg/m ³	10.0 mg/m ³	20 mg/m ³ (STEL)
Decabromodiphenyl Oxide	1163-19-5	15.0 mg/m ³	10.0 mg/m ³	5.0 mg/m ³ TWA 8hr. AIHA WEEL

* Substances listed in the hazardous Ingredients section are those that have been determined to be health hazards and are present at a concentration of 1% or greater, or 0.1% if the substance is on the list of potential carcinogens cited in the OSHA Hazard Communication Standard.

5010 River Road Mount Bethel, Pennsylvania 18343-5610 U.S.A.
Phone: (570) 897-8200 Fax: (570) 897-6081 Web: www.lamtec.com

SECTION 3- PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point: Not Applicable
Melting Point: Not Applicable
Vapor Pressure: Not Applicable
Vapor Density: Not Applicable
Solubility (in water): Insoluble In Water
Appearance: Foil-Scrim-Kraft Lamination (Foil or Black)
Odor: No Odor
Specific Gravity: Not Determined

SECTION 4- FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Applicable
Method Used: Not Applicable
Flammability Limits: LEL - Not Applicable
UEL - Not Applicable
Auto-Ignition Temperature: Not Applicable
Extinguishing Media: Foam, dry chemical, fog or water
Special Fire Fighting Instructions: Fires involving this product should be fought while wearing self-contained breathing apparatus.
Unusual Fire And Explosion Hazards: None

SECTION 5- REACTIVITY DATA

Stability: Stable
Hazardous Decomposition Products: Under fire conditions, products will decompose and produce hydrogen chloride, hydrogen bromide, carbon monoxide, carbon dioxide and other organic vapors.
Hazardous Polymerization: Should not occur under normal use.

SECTION 6- HEALTH HAZARD DATA / FIRST AID

EYE CONTACT: Direct contact will cause mechanical irritation.
Irrigate immediately with water for at least 15 minutes. Seek medical attention.

SKIN CONTACT: Direct contact can cause mechanical irritation.

SKIN ABSORPTION: Not likely to be absorbed through skin.

INGESTION: Not likely to occur under normal conditions.

INHALATION: Product cannot be inhaled in its normal form. If abnormal use creates dust, wear a NIOSH/OSHA approved respirator.

SIGNS AND SYMPTOMS OF EXPOSURE: None known.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known.

SECTION 7- PRECAUTIONS FOR SAFE HANDLING AND USE

SPILL PROCEDURES: Not Applicable

DISPOSAL METHOD: In accordance with applicable, local, state and federal regulations. When incinerating, use a unit with acid scrubber to remove hydrogen chloride and bromide.

SECTION 8- CONTROL MEASURES

VENTILATION: Not required for normal use.

RESPIRATORY PROTECTION: Not required for normal use. If abnormal use creates dust, wear a NIOSH/OSHA approved respirator.

SKIN PROTECTION: Not normally required.

EYE PROTECTION: Not normally required.

SECTION 9- SPECIAL PRECAUTIONS / ADDITIONAL INFORMATION

DOT INFORMATION: Not regulated by DOT

HAZARD CLASS: Non hazardous.

HMIS HAZARD RATING: HEALTH - 0, FLAMMABILITY - 1, REACTIVITY - 0

NFPA HAZARD RATING: HEALTH - 1, FLAMMABILITY - 1, REACTIVITY - 0

While the information and recommendations set forth herein are believed to be accurate, Lamtec Corporation makes no warranty with respect thereto and disclaims all liability from reliance thereon.