



**ANY JOB.  
ANY SIZE.  
ANY PLACE.**

60 Years of American Ingenuity

**2300**

The **2300** is specifically designed for the busy contractor who is increasing his business. Capable of blowing all types and brands of loosefill insulation to the manufacturer's specifications.

- Adaptable fold down loading door
- Removable all steel airlock allows quick access for maintenance
- User friendly electric dashboard
- Clear acrylic safety guard allows for easy inspection
- Durable powder coat finish
- Large hopper capacity for less reloading time
- Built in tool holder
- Optional 4 blower upgrade

**MATERIAL PRODUCTION RATE**

**MATERIAL**

<b>CELLULOSE</b>	<b>3000 (1361) *</b> <b>100 Bags per hr.*</b>
<b>FIBERGLASS</b>	<b>1000 (454) *</b> <b>33 Bags per hr.*</b>

\* lbs/hr (kg/hr) rating with 150 ft. (45.8 m.) of 3" (7.6 cm.) hose at 16 ft. (4.8 m.) elevation.

**NOTE:**

Manufacturer's product brand, density and variable blowing conditions will affect production rate.



Backed by a manufacturer's  
**2-YEAR WARRANTY - Made in the U.S.A.**

60 Years

KRENDL MACHINE COMPANY • 1201 SPENCERVILLE RD • DELPHOS, OHIO 45833 • 800.459.2069 • F 419.695.9301



1958-2018 krendlmachine.com



# KRENDL

The Innovator in Insulation Equipment™

# 2300

Scan to learn more about Krendl Machine

### • POWER REQUIREMENT •

Double input, 30/20 amps each/120 volt/60hz

Single input, 30 amp 240volt/60hz

International -Double input, 230volt/50hz

CE/CSA/CUL /UL

\* Optional 4 blower -Single Input , 50amp 240v/60hz

### • HOPPER CAPACITY •

40 cu. ft. (1.13 m<sup>3</sup>)

Loading made easy with built in adaptable tray

### • WEIGHT/DIMENSIONS •

800 lbs / 32.5"W x 68"D x 71"H

363 kg. / 83cm x 173cm x 180cm

### • BLOWER/SIZE •

14amp/2-stage (120volt)

Double Blower System yields

140 CFM @ 3 1/2 PSI per blower

### • AIRLOCK •

#### Slideout Airlock System

16" x 12" diameter

(40.6cm. x 30.5cm. diameter)

3" (7.6cm.) outlet

### • 2 HP Direct Drive Motor/Reducer •

w/overload protection



#### Electric Dashboard

- LED start & stop buttons
- Digital voltmeter
- Recessed power supply
- Digital hourmeter
- Dual variable blower speed controls



#### Dual Agitators

Designed for Constant Material Flow



#### Clear Acrylic Safety Guard

Allows for Inspection